

DUNLOP

Flexible

FC JOINTING COMPOUND



DUNLOP FC JOINTING COMPOUND is suitable for jointing fibre cement sheet and blueboard prior to coating with a decorative finish. This flexible premixed compound has excellent adhesion and is easy to use. Use DUNLOP COLOURED RENDER TEXTURE COAT as a decorative finish over fibre cement sheet or blueboard.

USE ON

Fibre Cement Sheet and Blueboard.

SURFACE PREPARATION

Ensure the surface is clean of dust, oil, grease, salt, mould, release agents or other contaminants that will interfere with adhesion. Surfaces must be dry. Protect and mask areas not being coated. Fixing of all fibre cement sheet and blueboard should be carried out as per manufacturer's instructions.

APPLICATION

Apply DUNLOP FC JOINTING COMPOUND to the sheet joint with a steel trowel. Whilst product is still wet, lay appropriate joint tape into the jointing compound. Apply a second coat of DUNLOP FC JOINTING COMPOUND over the taped joint and ensure the surface is levelled out to a feathered edge whilst the compound is still wet. When touch dry or within 4 hours, the joint finish can be lightly sanded to level off any excess jointing compound along the joints. Coverage will vary depending on the condition of the surface and site conditions.

COVERAGE

Coverage will vary depending on the condition of the surface and site conditions. As a guide, 3kg will cover approximately 21Lm and 8kg will cover approximately 56Lm at a 75mm width at a 1mm thickness.

DRYING TIME

Before application of a decorative finish allow to cure for a minimum of 1 day for each 2mm thickness of the patched render based on 23°C and 50% relative humidity. Drying times may vary in cold or humid conditions.

CLEAN UP

Clean all tools in water immediately after use.

SHELF LIFE

12 months when stored in the original unopened packaging, in a dry place at 23°C and 50% relative humidity.

PRECAUTIONS

DUNLOP FC JOINTING COMPOUND is not suitable for use over floors. Do not apply in temperatures below 10°C or above 30°C or in extreme conditions such as high wind or direct sunlight. Do not add additional water to the product.

SAFETY DATA

Avoid contact with skin and eyes; in case of contact with the eyes, wash out immediately with fresh running water. If irritation continues, seek medical attention.

Wear protective gloves, clothing and eye protection. Avoid inhaling dust/fume/gas/mist/vapours/spray. Ensure adequate ventilation during mixing and application. Store locked up. Check with your local Council regarding the disposal of contents. Keep out of the reach of children. Call the Poisons Information Centre on 131 126 (AUS) and 0800 764 766 (NZ) or call a doctor if you feel unwell. Additional information is in the Safety Data Sheet (SDS) at www.dunlopdiy.com

10 YEAR GUARANTEE

Ardex Australia Pty Ltd ("we" or "us") guarantees this product (also referred to as "our goods") is free from manufacturing defects and will perform to any applicable specification published by us for 10 years from the date of application of the product if such application occurs within this product's specified shelf life. Our liability under this guarantee is limited at our option to replacement of the product, repair of any damage to the immediate surface or area of application of the product, or the cost of such replacement or repair, in each case if we are satisfied loss or damage was due to a breach of this guarantee. This guarantee does not apply if damage or loss is due to failure to follow our published instructions or any act or circumstance beyond our control, including shade variations and efflorescence and faulty workmanship on the part of any installer or applicator of the product. If you wish to make a claim under this guarantee you must notify us (Address: 7/20 Powers Road Seven Hills NSW 2147; Phone: 1800 222 841; Email: technicalservices@ardexaustralia.com), identify the product and provide evidence of your purchase and the subsequent application of the product within 30 days of any alleged loss or damage occurring. We reserve the right to ask you for satisfactory evidence of any alleged loss or damage and to undertake any inspections and tests necessary to establish your rights under this guarantee. Any claim under this guarantee is at your cost. This guarantee is in addition to any rights or remedies you may have as a "consumer" under the Australian Consumer Law and to that extent you need to be aware that: "Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and for compensation for any other reasonably foreseeable loss of damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure".

DISCLAIMER

The technical details, recommendations and other information contained in this data sheet are given in good faith and represent the best of our knowledge and experience at the time of printing. It is your responsibility to ensure that our products are used and handled correctly and in accordance with any applicable Australian Standards. Our instructions and recommendations are only for the uses they are intended. Users are advised to confirm that this product is suitable for their application and conforms with the specifications of the system being employed and other products in that system. We also reserve the right to update information without prior notice to you to reflect our ongoing research and development program. Country specific recommendations, depending on local standards, codes of practice, building regulations or industry guidelines, may affect specific installation recommendations. The supply of our products and services is also subject to certain terms, warranties and exclusions, which may have already been disclosed to you in prior dealings or are otherwise available to you on request. You should make yourself familiar with them.

This datasheet was issued in November 2019 and is valid for 3 years, unless updated sooner. Always refer to www.dunlopdiy.com for the latest technical data from ARDEX Australia Pty. Ltd.