



FLOOR REPAIRER

Rapid Patch

DUNLOP FLOOR REPAIRER RAPID PATCH is a fast setting patching mortar that can be used on cracks and holes up to 20mm prior to laying tiles, vinyl or carpet floor coverings. It is ready to walk on in just 45 minutes and ready for floor coverings after 1 hour. Suitable over a number of surfaces including concrete, renders (walls), screeds, masonry, plasterboard, timber and fibre-cement sheet. Ideal for ramping from a feather edge to normal screed thicknesses.



If **DUNLOP FLOOR REPAIRER** is to be used as a wear surface, a suitable covering or paving paint is required. This product is to be used as a repair mortar only. If a self-levelling cementitious material is required, use **DUNLOP MULTIPURPOSE FLOOR LEVELLER** for concrete floors or **DUNLOP TIMBER FLOOR LEVELLER** for timber floors.

SURFACE PREPARATION

Surfaces must be solid, clean and free of wax, grease and all loose contaminating materials or coatings. Plasterboard, timber and fibre-cement sheet should be primed with **DUNLOP PRIMER** and allowed to dry. Other porous surfaces will not require priming. Direct to earth sub-floors, must be sealed with **DUNLOP DAMP-PROOF** prior to application.

MIXING

IMPORTANT: The mixed material is only usable for up to 15 minutes depending on ambient temperature so ensure that the surface is prepared for immediate application. In a clean bucket, mix 1.5L of clean water with 5kg of **DUNLOP FLOOR REPAIRER** to a smooth consistency, preferably using an electric mixing paddle. Only mix enough material that can be used within the 15 minute pot life.

APPLICATION

Use a trowel to apply the **DUNLOP FLOOR REPAIRER** to the surface and immediately smooth off. After approximately 15 minutes, trim off excess material and finish off with a wet trowel and use a sponge to eliminate trowel marks and obtain a smoother surface.

DRYING TIME

DUNLOP FLOOR REPAIRER will set after 45 minutes of application after which it can be walked on. Floor coverings such as vinyl, carpet and tiles can be installed after 1 hour at 23°C. High temperatures will accelerate the drying time whilst low temperatures will slow the hardening process.

COVERAGE

5kg of **DUNLOP RAPIDSET REPAIR MORTAR** will cover approximately 3m² at 1mm thickness or 1m² at 3mm thickness.

CLEAN UP

Clean all tools in water immediately after use.

SHELF LIFE

12 months when stored in a dry place, in original unopened packaging.

PRECAUTIONS

Do not apply in temperatures below 10°C or above 30°C. Low temperatures will extend the drying time of the mortar whilst high temperatures will shorten the pot life and drying time of the **DUNLOP FLOOR REPAIRER**. This is a repair product only, for larger areas or projects, use a Dunlop Floor Leveller suitable for your application. Not suitable for use with epoxy coatings.

*Not suitable for use as a wear surface where surface may be subjected to frost at any point in time. Product must be covered with a suitable floor covering such as vinyl, carpet, ceramic tiles or suitable paint. Not suitable for use in permanently wet areas.

SAFETY DATA

This product may cause irritation and an allergic reaction to the skin. It may cause serious eye injury and irritation to the respiratory system. In case of contact with the eyes rinse with running water (15 mins) including removal of contaminated clothing. Wear protective gloves, clothing, eye and face protection. Avoid inhaling dust, remove to fresh air. Ensure adequate ventilation during mixing and application. Store locked up. Check with your local Council regarding the disposal of contents. Keep out of the reach of children. Call the Poisons Information Centre on 131 126 (Aus) and 0800 764 766 (NZ) or call a doctor if you feel unwell. Additional information is in the Safety Data Sheet (SDS) at www.dunlopdiy.com

10 YEAR GUARANTEE

Ardex Australia Pty Ltd ("we" or "us") guarantees this product (also referred to as "our goods") is free from manufacturing defects and will perform to any applicable specification published by us for 10 years from the date of application of the product if such application occurs within this product's specified shelf life. Our liability under this guarantee is limited at our option to replacement of the product, repair of any damage to the immediate surface or area of application of the product, or the cost of such replacement or repair, in each case if we are satisfied loss or damage was due to a breach of this guarantee. This guarantee does not apply if damage or loss is due to failure to follow our published instructions or any act or circumstance beyond our control, including shade variations and efflorescence and faulty workmanship on the part of any

0216



FLOOR REPAIRER

Rapid Patch

installer or applicator of the product. If you wish to make a claim under this guarantee you must notify us (address: 7/20 Powers Road Seven Hills NSW 2147; phone: 1800222841; email: technicalservices@ardexaustralia.com), identify the product and provide evidence of your purchase and the subsequent application of the product within 30 days of any alleged loss or damage occurring. We reserve the right to ask you for satisfactory evidence of any alleged loss or damage and to undertake any inspections and tests necessary to establish your rights under this guarantee. Any claim under this guarantee is at your cost. This guarantee is in addition to any rights or remedies you may have as a "consumer" under the Australian Consumer Law and to that extent you need to be aware that: "Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and for compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure".

USER NOTES

The technical details and recommendations contained are given in good faith and represents the best of our knowledge and experience at the time of printing. It is the responsibility of the user to ensure that the products are used in accordance with Dunlop product instructions and in applications for which they are intended.