



Rapid

BOND COAT



DUNLOP BOND COAT is a water-based bonding coat that provides a chemical key to increase adhesion on smooth, dense, difficult non porous substrates prior to the application of DUNLOP adhesives, floor levelling compounds and DUNLOP undertile waterproofing membranes (in non-fully immersed situation). It can also be used on approved preformed shower bases prior to the installation of selected DUNLOP tiling and waterproofing systems. It is easy to apply, rapid drying and is suitable for internal and external wall or floor applications.

UNDER DUNLOP TILE ADHESIVES

Internal sheet timber (particleboard/plywood), medium density fibre-cement sheet, compressed fibre-cement sheet, jointing compound over plasterboard, Scyon™, concrete, renders, screeds, masonry and lightweight concrete blocks, autoclaved aerated concrete (AAC), existing glazed tiles (not suitable for shower floors or permanently immersed conditions).

UNDER DUNLOP FLOOR LEVELLERS

Internal sheet timber (particleboard/plywood), compressed fibre-cement sheets, concrete, masonry, lightweight concrete blocks, autoclaved aerated concrete (AAC), existing glazed tiles (tiles to be de-glazed before priming). Note: Not suitable for steel trowelled finish concrete where a floor leveller is being applied.

UNDER DUNLOP UNDERTILE WATERPROOFING MEMBRANES

Compressed fibre-cement sheets, concrete, masonry, render and screeds.

SUBSTRATE PREPARATION

The surface to be primed must be clean, firm and free of dust, dirt, oil, grease, curing compounds, release agents and degraded and unsuitable old surface coatings. Ensure surfaces are dry prior to application, with no residue or permanent dampness. Surfaces must be suitable for the application of the subsequent product being used.

APPLICATION

Stir the product well before use. Spread the material using a brush or long nap roller to cover at a rate of at least 6–10m² per litre over the entire surface to be primed. For floor levelling application and highly absorbent substrates dilute DUNLOP BOND COAT with water 1:1 by volume.

DRYING TIME

Ensure the DUNLOP BOND COAT is fully dry prior to the application of subsequent products, allow approximately 20 minutes at 23°C and 50% relative humidity. Type of substrate being primed, porosity and climatic conditions will affect drying times, allow longer for lower temperatures or high relative humidity.

COVERAGE

1 litre of DUNLOP BOND COAT will cover approximately 6–10m². Coverage will vary depending on the porosity of the surface and method of application.

CLEAN UP

Clean all tools in water immediately after use.

SHELF LIFE

DUNLOP BOND COAT has a shelf life of 12 months when stored in the original unopened packaging, in a dry place at 23°C and 50% relative humidity. Store away from direct sunlight. Replace lid tightly after use. Protect from freezing.

SAFETY DATA

Avoid contact with skin and eyes; in case of contact with the eyes, wash out immediately with fresh running water. If irritation continues, seek medical attention. Wear protective gloves, clothing and eye protection. Avoid inhaling dust/fume/gas/mist/vapours/spray. Ensure adequate ventilation during mixing and application. Store locked up. Check with your local Council regarding the disposal of contents. Keep out of the reach of children. Call the Poisons Information Centre on 131 126 (AUS) and 0800 764 766 (NZ) or call a doctor if you feel unwell. Additional information is in the Safety Data Sheet (SDS) at www.dunlopdii.com.



Rapid

BOND COAT

10 YEAR GUARANTEE

Ardex Australia Pty Ltd (“we” or “us”) guarantees this product (also referred to as “our goods”) is free from manufacturing defects and will perform to any applicable specification published by us for 10 years from the date of application of the product if such application occurs within this product’s specified shelf life. Our liability under this guarantee is limited at our option to replacement of the product, repair of any damage to the immediate surface or area of application of the product, or the cost of such replacement or repair, in each case if we are satisfied loss or damage was due to a breach of this guarantee. This guarantee does not apply if damage or loss is due to failure to follow our published instructions or any act or circumstance beyond our control, including shade variations and efflorescence and faulty workmanship on the part of any installer or applicator of the product. If you wish to make a claim under this guarantee you must notify us (Address: 7/20 Powers Road Seven Hills NSW 2147; Phone: 1800 222 841; Email: technicalservices@ardexaustralia.com), identify the product and provide evidence of your purchase and the subsequent application of the product within 30 days of any alleged loss or damage occurring. We reserve the right to ask you for satisfactory evidence of any alleged loss or damage and to undertake any inspections and tests necessary to establish your rights under this guarantee. Any claim under this guarantee is at your cost. This guarantee is in addition to any rights or remedies you may have as a “consumer” under the Australian Consumer Law and to that extent you need to be aware that: “Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and for compensation for any other reasonably foreseeable loss of damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure”.

DISCLAIMER

The technical details, recommendations and other information contained in this data sheet are given in good faith and represent the best of our knowledge and experience at the time of printing. It is your responsibility to ensure that our products are used and handled correctly and in accordance with any applicable Australian Standards. Our instructions and recommendations are only for the uses they are intended. Users are advised to confirm that this product is suitable for their application and conforms with the specifications of the system being employed and other products in that system. We also reserve the right to update information without prior notice to you to reflect our ongoing research and development program. Country specific recommendations, depending on local standards, codes of practice, building regulations or industry guidelines, may affect specific installation recommendations. The supply of our products and services is also subject to certain terms, warranties and exclusions, which may have already been disclosed to you in prior dealings or are otherwise available to you on request. You should make yourself familiar with them.

This datasheet was issued in November 2019 and is valid for 3 years, unless updated sooner. Always refer to www.dunlopdij.com for the latest technical data from ARDEX Australia Pty Ltd.