



# TILE-ALL *Plus*



**DUNLOP® TILE-ALL PLUS** is a single component, silane modified polymer adhesive and neutral curing sealant which is extremely flexible, with high initial tack and good bond strength. It is ideal as a general shower, kitchen and bathroom repair adhesive and sealant for replacing tiles, fitting accessories and finishing off joints. It can also be used in underwater applications, either applied to the immersed substrate or to the item to be fixed, making it ideal for minor repairs.

### USE

DUNLOP® TILE-ALL PLUS is ideal for bonding most construction materials including glass, tiles, ceramics, wood, plastic and metal. DUNLOP® TILE-ALL PLUS can be used for elastic joints between wood, plastic, metal and ceramic materials or for sealing expansion and connection joints. It is recommended that a trial application be conducted to optimise the conditions for particular applications.

### SUBSTRATES

Concrete, wall panels, timber, waterproofing membranes, ceramic tiles, aluminium, plastics, metal, polystyrene foam, glass and glazed tiles.

### SUBSTRATE PREPARATION

In general, the substrate or joint must be clean, firm and free of dust, dirt, oil, grease, curing compounds, old adhesive residues, paints and coatings, bitumen, tar, release agents and other barrier materials. For optimum performance, the substrate or joint can be slightly damp.

### APPLICATION

Remove aluminium seal at the bottom of the cartridge, pierce the protective membrane at the tapered nozzle, attach and trim nozzle to required size and place cartridge in applicator gun.

Apply DUNLOP® TILE-ALL PLUS in stripes to the substrate or to the item to be fixed. Press the items firmly together within 7-10 minutes (at a temperature of 20°C) and before skinning of the adhesive starts. If using the product for spot fixing repairs, ensure that the maximum distance between the glue points is 25 to 30cm and observe the weight of the item being fixed. Do not apply at temperatures below 5°C or above 35°C. The drying time depends on the substrate, climatic conditions and the materials being fixed. Higher humidity will shorten the open time while lower humidity will extend the open time. Close open cartridge and reuse as soon as possible. Note: Always remove a small layer of any skinned adhesive before reusing. If in doubt about characteristics, carry out a trial application. Spillage can be removed when wet, with a clean cloth.

### SHELF LIFE

12 months when stored in the original, unopened packaging, in a dry place at 23°C and 50% relative humidity.

### ATTENTION

DUNLOP® TILE-ALL PLUS achieves a good bond underwater. We recommend a trial application to ensure a good bond is achieved. The long-term stability when fixed underwater may vary depending on application. DUNLOP® TILE-ALL PLUS

can be over painted after drying with most commonly used paints; due to the vast range of paints and coatings on the market we recommend a small test area prior to proceeding. Do not use DUNLOP® TILE-ALL PLUS for chemical resistant applications.

### SAFETY

Use in well-ventilated areas. Avoid skin and eye contact. If uncured material makes contact with the eye, flush with clean water for at least 15 minutes and seek medical advice. In case of skin contact, first wipe the skin with a dry cloth then wash with soap and water. If respiratory discomfort is experienced, move to an area for fresh air. If swallowed, drink plenty of water in small portions, do not induce vomiting and seek medical advice. Keep out of the reach of children. Material Safety Data Sheet available on request. Dunlop is a trademark of Ansell Limited and is used under licence by ARDEX in Australia and New Zealand

### TOLL FREE HOTLINE

1800 222 841 (Aust) 0800 224 070 (NZ)

### USER NOTES

The technical details and recommendations contained in this data sheet are given in good faith and represent the best of our knowledge and experience at the time of printing. It is the responsibility of the user to ensure that the products are used in accordance with DUNLOP product instructions and in applications for which they are intended.

DUNLOP is a trademark of Ansell Limited and is used under licence by ARDEX in Australia and New Zealand.

ARDEX AUSTRALIA PTY LTD. ABN 82 000 550 005  
20 Powers Road, Seven Hills NSW 2147 Australia

### ARDEX Australia Pty Ltd

<b>NSW</b>	Ph (02)9851 9100	Fax (02)9838 7970
<b>VIC</b>	Ph (03)9308 9255	Fax (03)9308 9332
<b>QLD</b>	Ph (07)3817 6000	Fax (03)3881 3188
<b>SA</b>	Ph (08)8268 2511	Fax (08)8345 3207
<b>WA</b>	Ph (08)9256 8600	Fax (08)9455 1227

### ARDEX New Zealand Ltd

**Christchurch** Ph (03)3843 029 Fax (03)3849 779