

# CONCRETE RESURFACING

*Don't replace it,  
resurface it!*

## STEP 1:

## RESURFACE OLD CONCRETE WITH DUNLOP CONCRETE RESURFACER



**Use on:** concrete surfaces such as paths, patios, courtyards, walkways, driveways, garages, pool decks and most vertical surfaces.



### REPAIR AND PATCH

- Repair and patch minor holes, gouges or spalls (up to 25mm diameter and 12mm deep).
- For larger or deeper repairs use DUNLOP ARDIT CRACK FILLER.

**TIP:** RESURFACE DURING THE COOLER PART OF THE DAY. DO NOT RESURFACE WHEN DEW OR RAIN IS LIKELY.

Surface preparation is key, this is a summary and must be read in conjunction with the instructions on the packaging in-store and technical datasheet and SDS available on [www.dunlopdii.com](http://www.dunlopdii.com)



### APPLY

- Prime the concrete with DUNLOP MULTIPURPOSE PRIMER.
- Apply with DUNLOP ARDIT TROWEL, squeegee or broom.
- Thickness can be applied between 0.8mm – 3mm. Additional coats can be applied, prime in between coats.
- Coverage is 9m<sup>2</sup> at 0.8mm.
- Drying time is 2-4 hours. Drive on in 16-24 hours. Seal after 24 hours.
- For best results seal and protect with DUNLOP CONCRETE RESURFACER SEALER available in clear and can also be tinted to Jet Black, Charcoal, Concrete Grey and Burnt Terracotta.

Visit [www.dunlopdii.com](http://www.dunlopdii.com) for all your project needs.

 **DUNLOP**

# CONCRETE RESURFACING SEALING

*Seal and protect*

## STEP 2:

## SEAL AND PROTECT WITH DUNLOP CONCRETE RESURFACER SEALER



**Use on:** newly applied DUNLOP CONCRETE RESURFACER, existing concrete or previously sealed concrete to provide a durable, hardwearing 'wet look' sealer that protects and enhances concrete surfaces.

### SEAL

- Apply by brush, lambswool roller or low volume spray.
- Apply a minimum of 2 coats.
- Coverage is 8-10m<sup>2</sup> per litre, seals up to 16m<sup>2</sup> (2 coats).
- Touch dry in a minimum of 2 hours.
- Walk on in 3 hours and drive on in 24 hours.

**TIP:** TEST THE SEALER IN A SMALL AREA TO DETERMINE SUITABILITY FOR YOUR PROJECT.

Surface preparation is key, this is a summary and must be read in conjunction with the instructions on the packaging in-store and technical datasheet and SDS available on [www.dunlopd diy.com](http://www.dunlopd diy.com)

### HOW TO TINT DUNLOP CONCRETE RESURFACER SEALER

1. Pour the entire contents of your selected colour of the DUNLOP SEALER TINT 200ml into the DUNLOP CONCRETE RESURFACER SEALER 3.8L.
2. Stir well or lightly shake the sealed container.

DUNLOP SEALER TINT is available in Jet Black, Charcoal, Concrete Grey and Burnt Terracotta.



Visit [www.dunlopd iy.com](http://www.dunlopd iy.com) for all your project needs.

 **DUNLOP**