

TECHNICAL BULLETIN

INSTALLATION OF NEW SHEET VINYL OVER EXISTING RESILIENT SHEET OR TILE COVERINGS

INTRODUCTION & SCOPE

The commercial resilient sheet and tile flooring industry place many demands on contractors to save time and money by sometimes forgoing sound installation practices and requesting that new resilient coverings be installed over existing resilient sheet or tile coverings.

Whilst this practise is undertaken on a daily basis in the industry, contractors should be aware of the requirements of the relevant Flooring Standards, the flooring manufacturer, and the issues of adhering a non absorbent covering such as sheet vinyl, to a non-absorbent surface such as an existing resilient sheet or tile covering using water base adhesives.

THE AUSTRALIAN STANDARD

In referring to the current Australian Standard A.S.1884 2012 section 3.2.3 the following advice is provided:

“Resilient sheet and tile finishes are not considered a suitable surface for adhering resilient coverings”.

This is a significant change from the superceded 1985 version of the standard which said in section 2.2.2,

“Existing resilient sheet and tile

floors, which have a smooth surface and are well adhered may be considered to be a suitable surface for laying a new floor covering. Cushioned or loose laid floor coverings are not acceptable surfaces”.

THE BRITISH STANDARD

The current British Standard “B.S. 8203 : 2001/2009 Installation of Resilient Floor Coverings” section 3.5 provides these recommendations as follows:

“The practise of laying the floor coverings covered by the British Standard on top of existing sheet and tile floor coverings is not recommended. Existing floor coverings and sufficient residual of adhesive should be removed to enable the subfloor to receive the floor covering. The level of dryness of the base with regard to both rising moisture from the ground and residual moisture should be in accordance with section 3.1”.

RESILIENT FLOOR COVERING MANUFACTURER’S RECOMMENDATIONS

In addition to the recommendations provided in Flooring Standards, the vinyl flooring manufacturer’s recommendations must also be followed in such installations. To the best of our knowledge, the practice of installing sheet vi-

nyl over existing resilient sheet or tile covering’s is not widely recommended in Australia, or at best is not a preferred option.

THE TECHNICAL ISSUES

Where the installer decides they wish to proceed with an installation which while feasible runs counter to the recommendations, they need to consider the following things.

The old floor surfaces must be cleaned thoroughly to remove any polishes, varnishes, oils, or soaps etc., and then lightly sanded to create a slightly rough surface to assist the adhesive bond. Old sealers on existing vinyl can interfere with the performance of any levelling material or possibly even the adhesive bond of the new glue.

Glass reinforced backed PVC sheet must not be adhered to this type of surface, but because the acrylic adhesives required for these products rely on at least one of the bonding surfaces to be absorbent in order to cure properly, such material should be loose laid or perimeter fixed instead.

Adequate precautions should be taken when sanding existing resilient floor coverings as they may contain asbestos fibres. Inhalation of asbestos dust is detrimental to

TECHNICAL BULLETIN

health; removal is covered by local, state and federal government regulations.

Care must be taken with the selection of adhesives. If water based adhesives are used over existing resilient sheet or tile floors the adhesive may not dry out as moisture can be entrapped. water based adhesives now almost exclusively used in the flooring industry, require one absorbent surface for the moisture to migrate into so they can dry out. Consequently their use in this type of installation may result in the high risk of lifting or bubbling of the new sheet vinyl flooring;

Placing of vinyl over existing vinyl carries the risk of indentation and other surface damage. The old covering does not have the hardness or rigidity of concrete and so imposed loads such as chair feet, table feet, heavy trolleys or even high heeled shoes can produce unacceptable indentations.

Another consideration is any pre-existing moisture conditions which may not be evident, for example:

-Existing vinyl tiles, especially tiles manufactured with asbestos, may wick the moisture through the tile or allow moisture evaporation through the tile joint.

-Existing sheet vinyl coverings with Hydracord backing may also

wick moisture away through the porous backing.

Installing a new sheet vinyl over an existing vinyl covering without checking for any pre-existing moisture problems may result in bubbling/de-laminations of the new vinyl and expensive replacement costs.

SUMMARY

In summary the recommended procedures in line with flooring standards, and the recommendations of the flooring manufacturer would be to remove the existing vinyl flooring remove adhesive residue proceed with checking the subfloor for any pre-existing moisture condition apply the appropriate level of floor preparation (grinding, levelling, patching, skim-coating, etc) to achieve a smooth flat surface to meet the customers expectations.

DUNLOP recommends that old vinyl must be removed prior to new underlayment coverings being put down.

Notes

Always refer to the product data sheets for specific usage details.

The information contained herein is to the best of our knowledge true and accurate.

No warranty is implied or given as to its completeness or accuracy in

describing the performance or suitability of the product application.

Users are asked to check that the literature in their possession is the latest issue.

ARDEX AUSTRALIA PTY LTD,
ABN 82 000 550 005

7/20 Powers Road, Seven Hills,
NSW. 2147.